	[54]	PUP JOINT WITH INTEGRAL WING NUT RETENTION SHOULDER								
	[75]	Inventor: Paul A. Crawford, Stephenville, Tex								
	[73]	Assignee: FMC Corporation. Chicago. Ill.								
	[21]	Appl. No.: 962,182								
	[22]	Filed: Oct. 31, 1997								
	Related U.S. Application Data									
	[63]	Continuation of Ser. No. 651,646, May 22, 1996, abdoned.	an							
	(51)	Int. CL ⁶ F16L 19/0	12:							
		U.S. Cl 285/23; 285/354; 285/3 285/3	87							
	[58]	Field of Search 285/23, 354, 3	86							
		285/387. 388. 3	2							
[56] References Cited										
U.S. PATENT DOCUMENTS										
	1	86,021 6/1916 Mezfger 285/2	388							
	2	98,109 10/1942 Frank 285/3	388							
		/51,077 8/1973 Hiszpanski 285/3								
	4	16,477 9/1978 Waboski 285/3	}8€							

4,124,234	11/1978	Clark	285/388
4,575,044	3/1986	Gentry	285/388
4,648,634	3/1987	Kelch	285/387
4,877,270	10/1989	Phillips	285/387
5,160,174	11/1992	Thompson	285/387
5,362,109	11/1994	Pacnt	285/388

FOREIGN PATENT DOCUMENTS

723284	3/1980	U.S.S.R	285/387
17810	1/1914	United Kingdom	285/387

Primary Examiner—Eric K. Nicholson Attorney, Agent, or Firm—Henry C. Query, Jr.

[57] ABSTRACT

A pup joint is provided which comprises a length of pipe, a female sub integral with one end of the pipe and having external threads formed thereon, a male sub integral with the other end of the pipe, a wing nut for threadedly connecting the male sub to the female sub, a set of retainer segments for retaining the wing nut on the pup joint, and a retention shoulder formed on the male sub to maintain the wing nut and retainer segments on the male sub. In a preferred embodiment of the invention, the pipe and the male and female subs are comprised of a single forging, and the retention shoulder is formed by machining the male sub.

3 Claims, 2 Drawing Sheets

